

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Ref 2
G-44


METHOD OF CONTROLLING SUPPLY OF FUEL AND OXIDIZING AGENT

Patent number: JP60032254
Publication date: 1985-02-19
Inventor: SUGIMOTO TATSUSHI; others: 03
Applicant: SHINKOUBE DENKI KK; others: 01
Classification:
- international: H01M8/04
- european:
Application-number: JP19830139389 19830801
Priority number(s):

Abstract of JP60032254

PURPOSE: To minimize voltage fluctuation by supplying fuel and oxidizing agent when inclination similar to that of a load current - cell voltage curve is provided and the set value of such a voltage setting curve as located at the lower side of the curve is compared with the cell voltage and the difference becomes larger than the predetermined value.

CONSTITUTION: A control voltage set value C is made to be the same or similar to an inclination of a load current - cell voltage curve A. The set value C is expressed in the formula $V_r - k \cdot r \cdot I_L$. Provided that, V_r is a set voltage when the load current is 0A, I_L is the load current, r is a current detecting resistance and k is a constant which makes partial pressure of the voltage on both ends of current detecting resistance. Therefore, $V_r - k \cdot r \cdot I_L$ is compared with the cell voltage and when the difference becomes larger than the predetermined value, fuel and oxidizing agent are supplied. Then, cell performance with less voltage fluctuation can be obtained even when the load current is fluctuated.



Data supplied from the esp@cenet database - Worldwide

METHOD OF CONTROLLING SUPPLY OF FUEL AND OXIDIZING AGENT

Legal status (INPADOC) of JP60032254

No legal data found.